

Plockmatic - System 200e

Specifications



ACF & CF 510 Feeder/collator

No. of bins	10
Bin capacity	28 mm (1.1")
Sheet size, max	320 x 457 mm (12.6 x 18")
Sheet size, min	120 x 210 mm (4.75 x 8.25")
Paper weight, max	250 gsm (67 lb Bond)
Paper weight, min	50 gsm (14 lb Bond)
Collating speed	Up to 4000 sets/hour
Feeding speed	Up to 7000 sheets/hour
Centre registration	Yes
Air separation	Yes, on AC and ACF models
Error detection	Double feed, misfeed, empty bin, paper jam and stacker full
Receiving tray	Offset / straight stacking
Dimensions incl. base, H x W x D	1765 x 550 x 550 mm (69.5 x 21.6 x 21.6")
Weight	108 kg (238 lb)

BM 200e Binder

Capacity	30 sheets of 80 gsm (20 lb Bond)
Speed	Up to 3000 sets/hour
Sheet size, max	320 x 457 mm (12.6 x 18")
Sheet size, min	206 x 275 mm (8.1 x 10.8")
Paper weight, max	300 gsm (115 lb Cover)
Paper weight, min	64 gsm (18 lb Bond)
Automatic paper size set up in all machines from one control panel.	Yes
Stapling modes	Saddle stapling
Stapler heads	2
Staples	2 x 5000 Chisel pointed
Job saving	Yes, 10 jobs
Dimensions incl. base and belt stacker, H x W x D	1000 x 1420 x 670 mm (39.4 x 55.9 x 26.4")
Weight	130 kg (287 lb)

FTR 200e Trimmer

Capacity	30 sheets of 80 gsm (20 lb Bond)
Max booklet length, max trimming	220 mm (8,6")
Min booklet length, max trimming	123 mm (4,8")
Max booklet length, by pass	235 mm (9,2")
Min booklet length, by pass	105 mm (4,1")
Booklet width, max	320 mm (12,6")
Booklet width, min	120 mm (4,7")
Speed	Up to 1800 sets/hour
Trim length	Up to 15 mm (0,6")
Dimensions incl. base, H x W x D	910 x 350 x 620 mm (35.8 x 13.8 x 24.4")
Weight	65 kg (144 lb)

SQF 200e Squarefolder

Capacity	30 sheets of 80 gsm (20 lb Bond)
Paper size	Same as Trimmer FTR 200
Speed	Up to 1800 sets/hour
Squarefolding modes	4 + Auto and by-pass
Dimensions incl. base, H x W x D	910 x 350 x 620 mm (35.8 x 13.8 x 24.4")
Weight	52 kg (115 lb)

Plockmatic - System 200e

Power requirements

ACF & CF 510 Feeder/Collator

Voltage	Tolerance	Current	Frequency
100 V	-10 / +6%	4.8 A	50-60 Hz
110 V	-10 / +6%	4.8 A	50-60 Hz
120 V	-10 / +6%	4.8 A	50-60 Hz
127 V	-10 / +6%	4.8 A	50-60 Hz
220 V	-10 / +6%	2.4 A	50-60 Hz
230 V	±10%	2.4 A	50-60 Hz

BM 200e Binder, FTR 200e Trimmer & SQF 200e Squarefolder together

Voltage	Tolerance	Current	Frequency
100 V	-10 / +6%	4 A	50-60 Hz
110 V	-10 / +6%	4 A	50-60 Hz
120 V	-10 / +6%	4 A	50-60 Hz
127 V	-10 / +6%	4 A	50-60 Hz
220 V	-10 / +6%	2 A	50-60 Hz
230 V	±10%	2 A	50-60 Hz